

Cutting Attachments



Model 362 LIGHT/MEDIUM DUTY

A well designed robust attachment with outstanding cutting capacity of 75mm. Sets the standard for smaller torch use.

Features include- Wt. 0.4kg

- ▶ Head/body in solid forged brass
- ▶ Triangular stainless steel gas tubes for maximum strength and safety
- ▶ Equal pressure mixing
- ▶ Solid brass lever with stainless steel plunger
- ▶ Unique tapered 'O' ring sealing for safety
- ▶ Suits all gases

362 Contractors Cutt Att. Acetylene/Propane. To suit Harris Handle 019038

Note: Tip nut is 9008437

AVAILABLE
IN POP
HANG
SELL



Model 733/493F HEAVY DUTY

A truly professional cutting attachment suited for the toughest workshop conditions. Its many features are unmatched by other manufacturers.

Features include- Wt. 0.8kg

- ▶ Triangular stainless steel gas tubes for maximum strength, safety and operator comfort
- ▶ Tapered 'O' ring sealing for longlife/safety
- ▶ Accessible injector allows simple change - over to other gases
- ▶ Cuts to 150mm
- ▶ Accepts flat seating tips, greatly reducing head popping
- ▶ Positive pressure mixing. Fuel gas 40kPa (733)
- ▶ Universal pressure mixing. Fuel gas 1.5kPa (493F)
- ▶ Head, lever, body solid brass for long life
- ▶ Ease-on built in for better starts and piercing

493F Professional Cutt Att. **Propane, LPG, Natural Gas** to suit Harris original Handle 632, 043013

Note: Tip nut to suit both is 6259B

733 Part of the classic series, medium pressure **Acetylene** cutting attachment. The tough solid construction surpasses others in the market. Cuts to 100mm.

Made
in
Europe

Spare parts are
available for all
products