

Cutting Tips



Oxy/Acetylene

These two piece tips are very popular. Their flame characteristics, plus the ease of cleaning, make them ideal for Plumbers, Panel Beaters and other Contractors.

To suit 362 Cutting Att.

	Size	Precision Series
3690	00AC	Cuts 0-6mm Steel
3690	OAC	Cuts 6-13mm Steel
3690	1AC	Cuts 13-25mm Steel
3690	2AC	Cuts 25-75mm Steel

AVAILABLE
IN POP
HANG
SELL



Oxy/Acetylene

This Professional tip offers exceptionally quick starting for the operator. Combined with the ability to pull apart for cleaning. The flat seating allows easy reseating on-site with a rub with wet/dry - **a very unique product.** This flat seating tip greatly reduces the occurrence of tip popping. Precise gas flutes control the amount of gas being used.

Made
in
Europe



To suit 492 Cutt.Att., 142 & 624L Torches

	Size	Professional Series
6290	000	Cuts 0-5mm Steel (One pce copper)
	00AC	Cuts 5-10mm Steel
	0AC	Cuts 10-15mm Steel
	1AC	Cuts 15-25mm Steel
	2AC	Cuts 25-50mm Steel
	3AC	Cuts 50-100mm Steel
	4AC	Cuts 100-175mm Steel
	5AC	Cuts 175-250mm Steel
	6AC	Cuts 250-300mm Steel

NOTE: Standard 5mm Hose does limit good cutting to 100mm. For thicker steel, use larger diameter Hose.