

## Heating Tips

### Oxy/Acetylene

Heating with Oxy /Acet is used in industry in many different applications. When using the J633 and above, that procedures and methods become critical. Contact **Harris** for advise.

We believe our heating tips are the hottest in the industry.



J633



#### Size

J63	2	Multi Flame Heating
J63	3	Multi Flame Heating
J63	4	Multi Flame Heating
J143	5	Multi Flame Heating

- NOTE:**
- 1) Tip is silver soldered to stainless steel Tip Tube. Comes as a complete item (J633 & J634, J1435).
  - 2) Size 2 (copper) suits E43 Mixers.
  - 3) Sizes 3 & 4 (as shown in photo) suit E243 Mixer only.
  - 4) J632 can be fitted to H192E Mixer by using 190111 Adaptor.
  - 5) J633,4 will cause some problems with 5mm hose - (restricts flow). Suggest 8/10mm hose and manifold Acetylene cylinders.
  - 6) J1435 requires 10mm Hose and manifold Acetylene cylinders.

### Professional Oxy/Propane

The shape, performance, and characteristics of the flame are effected/controlled in some way by the tip. Harris tips are designed and manufactured to give the very best flame. Our quality is assured, as every tip is flame tested.

#### Size

2290	1H	Multi Flame Oxy/Propane Heating Tip
2290	2H	Multi Flame Oxy/Propane Heating Tip
2290	3H	Multi Flame Oxy/Propane Heating Tip
2290	4H	Multi Flame Oxy/Propane Heating Tip
2290	5H	Multi Flame Oxy/Propane Heating Tip



- NOTE:**
- 1) Tip Tube 2393 is needed, as well as the correct Mixer - F43 Propane/LPG, B43N Natural Gas.
  - 2) Standard 5mm Hose limits size to 2290 1H, 2H, 3H.
  - 3) Enormous heat is available with the above range of Tips.

#### Size

H62	1P	Heating Tip
H62	2P	Heating Tip
H62	3P	Heating Tip

**NOTE:** 1) Can attach to Professional Cutt Att. and Hand Cutting Torches.



- 23573 Nipple - Use with 2393 Tip Tube before fitting heating Tip for protection of the threads
- 23579 Adapts 2290 Heating Tips to Competitors S/S Tip Tubes