



Harris Products Group  
Since 1905

Turn to the **PROS.**



# Harris Gas Equipment for Heavy Industry

*Hand Cutting Torches for Fabricators, Demolition, Foundries, Scrap & Recycling Industries.*

**Model 625 Cutting Torches:** 300mm cut capacity, Available in 90\* & 180\* head, Various lengths 565mm-2,000mm available, 3 stainless steel tube design for performance and durability, Complies with ISO5172, Ease on Cutting Valve for better starts, accepts HARRIS flat seating tips, Flash-guards included (complies with AS4839).

Part Number	Description MODEL 625 Oxy/LPG or Oxy/Natural Gas. LPG or Nat Gas Pressure 20-50kpa
062Z084	90 degree head, 565mm long.
062Z084180	180 degree straight head, 565mm long
062Z088	90 degree head, 1000mm long
062Z066	180 degree straight head, 1000mm long
062Z106	90 degree head, 1250mm long
062Z106B	180 degree straight head, 1250mm long
062Z107	90 degree head, 1500mm long
062Z107B	180 degree straight head, 1500mm long
062Z109	90 degree head, 2000mm long
062Z10918	180 degree straight head, 2000mm long

**Straight Head Cutting Torch**

**90 Degree Head Cutting Torch**



## Harris Cutting Tips

**TIPS – HARRIS FLAT SEATING**

**2 Piece Tip for easy cleaning & prolonged tip life.**

**NX Series tip:** Chrome Jacket, General Purpose, Oxy/LPG and Oxy/Natural Gas.

Fuel 20-50 KPA



Part Number	Cut Capacity	Oxy Pressure
0NX	10-15mm	150-250kpa
1NX	15-25mm	200-350kpa
2NX	25-50mm	300-450kpa
3NX	50-75mm	300-450kpa
4NX	75-150mm	350-550kpa
5NX	150-200mm	450-550kpa
6NX	200-300mm	500-650kpa

# Harris Gas Apparatus for Heavy Industry

## CUTTING TIPS



Turn to the **PROS.**

**NFF Series Tip:** Heavy Preheat for cutting steel with rusted, painted or heavily scaled surfaces- Fast Starts. Chrome Jacket, Oxy/LPG and Oxy/Natural Gas. Fuel 20-50 KPA

Part Number	Cut Capacity	Oxy Pressure
3NFF	50-75mm	300-450kpa
4NFF	75-150mm	350-550kpa
6NFF	200-300mm	500-650kpa

**NFFL Series Tip:** Extra Long, 200mm for difficult access, Heavy Preheat for cutting steel with rusted, painted or heavily scaled surfaces – Fast Starts, Unplated heavy shell, Oxy/LPG and Oxy/Natural Gas. Fuel 20-50 KPA

Part Number	Cut Capacity	Oxy Pressure
150155	15mm-25mm, 1NFFL	250-350kpa
1501053	25mm-50mm, 2NFFL	300-450kpa
1501051	75mm-150mm, 4NFFL	350-550kpa

**NH Series Tips, HEAVY DUTY,** Heavy Preheat for cutting steel with rusted, painted or heavily scaled surfaces- Fast Starts, Unplated, Heavy Shell. Oxy/LPG and Oxy/Natural Gas. Fuel 20-50 KPA

Part Number	Cut Capacity	Oxy Pressure
6NH	250-275mm	420-500kpa
7NH	275-300mm	420-500kpa
8NH	300-380mm	420-500kpa



*Buy locally for the best service & support.*

**Harris Products Group  
HGE PTY LTD**

Brisbane | Melbourne | Perth | New Zealand  
14 Queensland Rd, Darra, QLD 4076  
Phone: (07) 3375 3670 | Fax: (07) 3375 3620  
Email: sales@hgea.com.au  
[www.harrisproductsgroup.com.au](http://www.harrisproductsgroup.com.au)  
Email NZ: sales@harrisnz.com  
[www.harrisproductsgroup.co.nz](http://www.harrisproductsgroup.co.nz)